

THE FASCINATION OF WOOD

Out of love for wood, the successful brand SERRA (lat. Saw) was founded in 1990 by the Bavarian founding family Fritz.

For almost 30 years now, the innovative company has been renowned for its high-quality, "Made in Germany" products. Since the beginning of 2019 SERRA is part of the Austrian WINTERSTEIGER AG.

The unique SERRA technology is now available in over 80 countries successfully in daily use. From the small mobile sawmill to the complete sawmill line we offer for every need and purse in the most different climate zones customized solutions.

The award "Top 100 Innovation Prize" is impressive proof of our lasting innovative strength.


We are proud of our first-class, worldwide personal service. Further machines for Wood completes our product range. The love for wood accompanies us everywhere: We work in wooden buildings, heat with wood and process wood. We are therefore well versed in this valuable raw material and this is the right basis for building excellent machines.

Convince yourself of us. We look forward to seeing you!

Your SERRA Team








SERVICE & SALES WORLDWIDE




www.sawmills4us.com/company/distributors




- Industrial also for very large logs up to 64 inches in diameter
- Extremely robust design with no weight restrictions on the equipment
- Higher throughput with lower investment costs
- Increased ease of operation because of tailor-made mechanization
- Supplementary machines for automated processes possible (project planning)
- All SERRA sawmills are available stationary (except XT 135)





- Flexible in use with diameters of up to 52 inches
- From the entry-level model to the premium giant (XT135)
- On the way from order to order in shortest possible time
- No long and costly raw material transports
- Mainly for custom cutting
- Increased operating comfort thanks to matching cabin
- All SERRA sawmills are mobile available (exception XE 160, XE 135, FE 50)
- Also available with petrol engines (KB)





POWERFUL SAWMILLS

Horizontal band saw mills are the core competence of SERRA. Four different size classes are available. Allowing you to mill logs with a maximum diameter of 36", 43", 52" or even 64", mobile and stationary.

SERRA's mobile sawmills in various weight and size classes are mostly used for custom cutting. Long hauls for logs can be prevented. For independence from the power grid, we also offer individual models with diesel or petrol engine, or you can work with a generator.

Furthermore: hot dipped galvanized frames (KE 90 / KB 90 / ME 110) at mobile sawmills, high-quality stainless steel log supporters in each model avoid blue coloration while cutting acidic wood, two possible feeding systems (hydraulic or electric) and a angled cut, which facilitates the cutting into the log and increases the speed (except FE50).












XE 160 / XE 135

- For heavy logs with up to 52" / 64" in diameter
- Extremely robust and heavy built
- Variable saw head with a lot of space above the saw blade
- Convincing additional equipment
- Comfortable access to sawblade with hydraulic cover opening
- Optimized for project planning
- Various optional operator stand solutions



Technical data	XE 160	XE 135
Log length*	from 28" - 19.6 feet	from 28" - 19.6 feet
Log diameter	64.2"	52.3"
Space above sawblade	27"	19"
Space below sawblade	54"	44"
Width of cut	55"	39"
Performance / 8 h**	15,000 BF	14,000 BF
Main engine	43 hp electric	30 hp electric
	60 hp electric	43 hp electric

Dimension of sawblades	XE 160	XE 135
Width	6"	4.75" - 5.5"
Thickness	0.051"	0.043" - 0.047"
Lenath	280" - 300"	217" - 237"

^{*} longer on request

XE 160 / XE 135







^{**} Dependent on diameter of log, board dimensions and number of helper



XT 135

- For heavy logs with up to 52 inches in diameter
- Big cutting length because of hydraulically foldable extension
- Variable saw head with a lot of space above the saw blade
- Comfortable access to sawblade with hydraulic cover opening
- Comfortable, lockable operators stand with protective roof
- Various cabins available



Technical data XT 135

Log length*	from 28 inches - 32 feet*
Log diameter	52.3"
Space above sawblade	19"
Space below sawblade	44"
Width of cut	39"
Performance / 8 h**	14,000 BF
Main engine	25 hp electric 30 hp electric

Dimension of XT 135 sawblades

Width	4.75" - 5.5"
Thickness	0.043" - 0.047"
Length	217" - 237"

^{*} longer on request


XT 135







^{**} Dependent on diameter of log, board dimensions and number of helper



SL 130i

- For heavy logs with up to 51" in diameter
- Award winning, proven technology for many years
- Variable saw head with a lot of space above the saw blade
- Two possible feeding systems: hydraulic or electric
- Comfortable V-Cockpit



Technical data

SL 130i

Log length*	28" - 52 feet mobile
Log diameter	51.5"
Space above sawblade	19"
Space below sawblade	44"
Width of cut	39"
Performance / 8 h**	14,000 BF
Main engine	25 hp electric 30 hp electric

Dimension of sawblades

SL 130i

Width	4" - 4.75"
Thickness	0.043" - 0.047"
Length	217" - 237"

^{*} longer on request

SL 130i







^{**} Dependent on diameter of log, board dimensions and number of helper



ME 110

- For heavy logs with up to 41 inches in diameter
- Convincing additional equipment
- Customer-specific frame division through innovative basic frame concept
- High-quality corrosion protection due to hot-dip galvanized base frame



Technical data

ME 110

Log length*	28 - 29 feet mobile
Log diameter	41.9"
Space above sawblade	20"
Space below sawblade	34"
Width of cut	32"
Performance / 8 h**	11,800 BF
Main engine	25 hp electric
-	30 hp electric

Dimension of sawblades

Width	4" - 4.75"
Thickness	0.043" - 0.047"
Length	224"

ME 110









^{*} longer on request

^{**} Dependent on diameter of log, board dimensions and number of helper



KE 90 / KB 90

- For heavy logs with up to 36 inches in diameter
- Two main drives options are available: Electric or air cooled V2 petrol engine from Vanguard.
- Convincing additional equipment
- Innovative base frame concept
- Customer-specific frame division through innovative basic frame concept
- High-quality corrosion protection due to hot-dip galvanized base frame
- Manual blade tensioning



Technical data

Log length*	28" - 32 feet mobile
Log diameter	34.8"
Space above sawblade	16"
Space below sawblade	33"
Width of cut	29.5"
Performance / 8 h**	7,600 BF
Main engine	25 hp electric 35 hp petrol


Dimension of sawblades

Width	3.15"
Thickness	0.039" - 0.047"
Length	201"

^{*} longer on request


KE 90 / KB 90







^{**} Dependent on diameter of log, board dimensions and number of helper



FE 50

- For logs with up to 19.68" in diameter
- 5 hppower engine
- Operator is not located on the side of the emerging sawdust
- Innovative sawblade concept with metal band sawblades of bimetal. No sharpening.
 No tooth setting.
- Easy to operate
- Extendable with 88 inches long extensions
- Low purchase price at high productivity at the same time.



Technical data

Log length*	24" - 141"
Log diameter	21.6"
Space above sawblade	7"
Space below sawblade	18"
Width of cut	15"
Performance / 8 h**	2,000 BF
Main engine	5 hp electric

Dimension of sawblades

Width	1.375"
Thickness	0.035"
Length	122"

FE 50








^{*} longer on request

^{**} Dependent on diameter of log, board dimensions and number of helper



Toe boards with clamps


- levels the log in a way that its centre is parallel to the sawing bed.
- clamp the log with their height adjustable clamps.
- pulls the log down against the log supporters.
- lower priced variant: clamps without leveling function of the log

MODULES / EQUIPMENT

Different hydraulic tools available for all models in order to optimize the handling of logs. Compile your machine individually or choose between Basic or Master package.


You have the choice. Of course we can assist you in what components you need for your needs. We can discuss not only the required number of tools, rather also the position in the frame they can be mounted. In doing this we make your sawmill more user friendly which in turn will increase your productivity and success.

On this double page we will show you a selection of possible hydraulic modules.




The log clamp turner / log turning assistant

- turns and clamps the log without damaging it.
- particularly flexible also at special cuts like wedges, multiple sided beams, etc.
- useful in combination with the log turning assistant, which prevents a possible roll back of the log while repositioning the log clamp turner.



The roller drums

- moves the log back and forward to the right position on the sawing table.
- can move the milled lumber to the end of the mill.
- by using spiral rollers the lumber can be moved laterally
- not powered, lower priced variant possible



Chain turner / lateral arms

- The chain turner and lateral arms move the milled lumber laterally on to the lateral arms beside the mill.
- Chain turners allow fast turning of small and medium sized logs.




The log lifter

- two different variants: At heavy machines, the log lifters are supported by the frame. At the lighter machines the log lifters are supported on the ground, can be placed according to the length of the logs and in order to transport the mill, you just lift and fold them up.
- depending on the model, logs with a weight up to 10 t can be lifted up to the sawing bed.



The board remover

- Receiving the waste and side boards by turning the log with your turning system.
- With the help of chain turners or the laterial arms in the frame the milled lumbed gets pushed onto the board remover.
- By lifting up the board removers the cutted wood falls down to the ground or stays on it or gets forwarded onto a buffering station. You decide which version fits best for you.



The squaring arms

- prevent the log from rolling off while loading and turning.
- are required for 90 degrees angeled lumber. The angle is adjustable.
- the squaring arms surveillance of the PLC avoids any unintentional damage.



Log feeders

Hot dipped galvanized, hydraulic driven, connected to the sawmill and operated from it. More units are posible.

STANDARD EXPANSION MODULES/ MATERIAL HANDLING

The following standard modules are available for facilitating the flow of wood on the log band saw. All modules are operated by the operating company of the sawmill. Ejectors and unwinders are also available for mobile sawmills, with cutting unwinders being foldable.



Log feeders

Extreme heavy built log feeders, hot dipped galvanized, electric driven, 30t capacity, operated from the sawmill. More units are posible.



Log feeder with buffering station and separator


Heavy built, hot dipped galvanized, electric driven conveyor chain. Separation hydraulically.



Conveyor belt

(13,12 ft) with conveyor (19,68 ft) hydraulically height adjustable

optional with board brushes




Board brush above

- hydraulically board
- height adjustable



Board brush below

Expensive woods must be cleaned of sawdust before drying. This is what the brush system is used for, which are installed on the roller conveyors or conveyor belts.




Board transporter with separator and collector station

Transfers the boards from the receivers of the mill to the collector station and separates the boards. Measurements on request. Price valid for complete unit. More available on request.




Buffering station

For collecting the boards before they are transported to the next machine.



Push-back system

- another cuttings removal variant is the push-back system.
- each board is taken along by the returning saw head after cutting.
- next, the system forwards these to a conveyor belt, which transports the boards directly to the resaw.



Reinforced buffering station

Function as above mentioned at buffering station, with adjustable height and angle.





Manual conveyor


Stable built, hot dipped galvanized, to transport the boards to the next working station.



Driven conveyor

Stable built, hot dipped galvanized, to transport the boards to the next working station. Electric driven.

OPERATORS STANDS



Luxury cabin ProComfort Plus

- spacious, insulated and noise proofed
- height adjustable up to max. 61 inches
- comfort seat can be moved sideways 19 inches
- two glass doors
- Note! The cabin is not suitable for container transport



Multifunctional cabin mobile

- insulated and noise proofed
- hydraulically foldable
- comfort seat
- glass door



V-Cockpit mobile Maxi

- controls arranged in an ergonomic way
- four rows of hydraulic levers for max. equipment
- combinable with big mobile cabin



Cockpit stationary

- decoupled from the machine
- comfort seat
- hight adjustable, if required



Stand-alone version

- decoupled from the machine
- ideal for building your own cabin around it



Big mobile cabin

- safety glass
- foldable roof
- lockable operators stand



Foldable cabin mobile

- completely folded forward onto the sawing bed for transport.
- light-weight aluminum construction




SETWORKSSERRA PROCOMFORT PLUS


Big full HD display with 21.5"

- touch control with all current cutting programs
- two joysticks with user defined function layout
- fire button for quick change of the function layouts
- batch-capability, that means programming of recurring functional processes. (e.g. unloading) starts by pressing the button.
- speedometer (Cutting speed)
- Squaring arms surveillance, pedal return of the sawhead and fully automatic milling possible

SERRA COMFORT PLUS







- Squaring arms surveillance, pedal return of the sawhead and fully automatic milling possible
- removable for transport



SERRA COMFORT

TFT Display


 same as SERRA Comfort Plus, but without joystick

SERRA BASIC PLUS



7 segment display


- keyboard: foil
- cutting program single board
- cutting program stack
- Unit of measurement metric / inch selectable
- integrated digital amperemeter
- Cutting programme chain gauge with 4 memory locations




With a SERRA sawmill, you can produce all needed products like edged boards, lathes, cants and beams with a single machine. Business is growing after a little while? Extend your technology with a resaw!

A resaw does not replace your main mill, but it will significantly relieve it

With a powerful resaw from SERRA the output increases enormously. Boards can be edged by our Duett/Quartett dual-trimmers, for example. If you are producing board material or even slats, you may be interested in our multi-head band resaws and if there is a need of really very high production have a look at the multirip resaw CS 600 with main engines up to 120 hp.






CS 600

High performance multirip resaw with innovative circular saw technology.

The heavy built design consists of two 0.590" thick lasered and mill-cuted steel plates. Between them, the whole machine is built up. Chain and V-belt drives are mounted externally.

The speed of two separately controlled feeding systems is adjustable via a frequency converter. The height is adapted hydraulically to the wood. Spacious opening to the hardened saw shaft for easy saw blade changing. Unlike most other multirip resaws on the market the saw shaft is supported only twice.

Therefore very precise and quiet. Central lubrication! Optional conveyor belt for lateral saw dust transport.



Technical data


Pass through width max	. 23.6"
Pass through height	6.25"
Cutting length min.	34.5"
Saw shaft	hardened, located under
	the wood, turns against
	feed direction
6 driven feed rollers	
Diameter of circular	
saw blades	13.75" - 19.5"
Main engine	30 hp - 120 hp
Saw shaft speed	2,400 rpm
Feeding speed	
(adjustable)	0 - 118 ft per/min.
Working height	33.4"
Width	5.25 feet
Length	10.5 feet
Height	5.25 feet
Weight (max.)	7,275 lbs

CS 600










MK 402 TO MK 405

Depending on the number of desired sawheads

The multi-head sawmill from SERRA is used as a resaw for boards and slats.

Energy efficient - productiv - resilient

The benefit against a circular resaw is, that the cutting kerf is much thinner. Because of that less precious wood will be transformed into sawdust, furthermore the power requirement is lower. In contrast to the main sawmill not the sawhead is moving back and forth along the log. Instead of that, the sawhead is static and the lumber gets pushed through.



Technical data

Log length	47" - infinite
Width of cut	15.75"
Height of cut	0.27" - 15.75"
Performance per	
sawhead	15 hp / 25 hp
Feeding speed	0 – 114 ft per/min

Dimension of sawblades

Width	3.15"
Thickness	0.039" - 0.047"
Length	201"

MK 402









DUETT / QUARTETT

A resaw with two (Duett) or with four (Quartett) circular saw blades can be the perfect addition for your sawmill. Simple but strongly built. Available as a mobile or stationary machine. A corrosion resistant construction made of aluminium and many galvanised parts guarantees long-term value retention.

Quick set-up and dismantling of mobile version. Particularly popular with stationary sawmills as a circular resaw. Innovative rubber wheels ensure high adhesion even with icy boards. The board width is adjusted via a driven spindle. The distance of the saw blades is displayed on a scale. Setwork available.



Technical data

Height of cut	to 2"
Width of cut	2" - 16.75"
Pass through width	0.0039"
Length of deck:	
Infeed	16.4'
Outfeed	10.5′
Length of board	unlimited
Weight	640 lbs / 900 lbs
Engine	electric (2 x 6.7 hp/
	3hp feed)
Plug	32 Ampere

DUETT / QUARTETT









As with all cutting technologies, the sharpness of the tool is of great importance.

The "Shark" series of grinding machines offers innovative technology. Tensioning and levelling devices complete the sharpening room.

We also offer generators as an addition to our saw mills. Producing your own electricity enables you to work with an electric-driven SERRA saw mill independently from the power grid.





SHARK 200

A precision machine which is particularly easy to use. The Shark 200 is an innovative new development in the field of dry grinding. With integrated extraction. The patented device has a large grinding wheel with a diameter of 300 mm.

The basic configuration already includes a diamond dresser mounted on a swivel arm. This means the disc maintains the same profile and ensures absolute precision at all times. No conversion work is required if a different tooth pitch or shape is to be ground. Simply change the cam and continue sharpening. Large scale for quick and easy adjustment of the cutting angle.

Innovative new development in the field of dry grinding

The balanced grinding wheel causes almost no vibrations, resulting in a better grinding pattern (similar to wet grinding machines!) while also significantly minimizing the risk of cracks in the blade! Easy balancing of the grinding wheel with

the included balancer. Optimum adjustment of the feeding speed through frequency converter. As standard with counter and automatic switchoff function.



Technical data

Engine	Grinding 1,4 kW
	Feeding 0,18
	Extraction 0,16 kW
Grinding wheel	300 x 10 x 76,2 mm
Feeding speed	stepless adjustable
Selective cam	Standart is PCP or PV,
	a lot more are available
Tooth pitch	from 15 to 55 mm
Weight	205 kg
Plug	16 Ampere CEE-plug

SHARK 200









SHARK 100

The precision of the Shark 200 is considered one-of-a-kind on the market compared to other dry grinding machines.

Not even the Shark 100 can match this accuracy. But something else makes it rather unique: With a weight of only 152 lbs it is easy to transport and can always be brought along when on the road with a mobile band sawmill from SERRA. This means that dull saw blades can be resharpened already during the day. If the sharpener stays at home, the resharpening has to be done after work.

Shark 100 - The perfect companion for the road

The compact design and excellent transport properties make the Shark 100 a very popular unit. The black handle bar on the left is used to adjust the tooth height. The handle bar on the right is used to position the height of the circumferential rods. The feed pawl is set in the center at the front.



Technical data

0.33 hp
200 x 8 x 32 mm
30 teeth per minute
PCP, PV
from 15 to 45 mm
152 lbs
16 Ampere
CEE-connector

SHARK 100









SERRA TENSIONING BENCH & SERRA BLADE ROLLER UNIT

The surface of the large cast wheels are curved with a small radius (crowning) on which the saw blades runs on. This is necessary so that your saw blade does not slide off the wheel towards the rear during high cutting speeds. For this purpose, the saw blade must be tensioned and aligned.

At SERRA new saw blades are ready to use on your crowning.

Depending on the width of the saw blade, it needs to be re-rolled sooner or later. The SERRA crowning is designed so that this is only necessary when the stellite tips are completly worn down if used properly. We would be glad to advise you on whether acquiring a tensioning bench makes sense for you. The significantly cheaper SERRA blade roller unit usually suffices. Without removing the saw blade from the machine, the planarity can get aligned. Please ask us. We would be happy to help you.

SERRA TENSIONING BENCH



SERRA BLADE ROLLER UNIT



Milling independently with us

GENERATORS

Generators make you independent. For fast and exact execution of jobs at any location. Generators ensure permanent and maintenance-free operation of all electric driven components in your sawmill. Exhaust free and noise reduced working.

The models can be set up in some distance.



Fuse protection

Weight

Emission-free and low-noise working

For many sawyers it is important, that the generator is very light. This usually is achieved with high-speed motors, which are very noisy, have a shorter lifetime and a higher consumption. Our SERRA generators are equipped with diesel engines with various capacities, which are connected with slow running (1.500 rpm.) generators. Each model is covered with a sound protection hood. Customers who have the smallest generator with 44kVA reported that it consumes only 2 - 3 liters diesel per hour.

Fuse protection

Weight

Dieselgenerator	· 44 kVA	Dieselgenerator	65 kVA
Technical details		Technical details	
Performance	44 kVA	Performance	65 kVA
Rev / Min	1.500 U/min	Rev / Min	1.500 U/min
Engine	water cooled diesel	Engine	water cooled diesel

16 and 32 A CEE


840 Kg

DIESELGENERATOR

1.030 kg

16, 32 and 64 A CEE





SPECIAL MACHINES FOR FORESTRY

For very sophisticated applications in the forestry, SERRA provides special solutions in high quality, that are practice-oriented and technically on the highest level.

The CutCoach is already used in many countries. Its an important and useful training device for wood workers that have to cut down tensioned trees by chain saw after storms.

The IronHorse do not only enable you to move out logs from the forest, especially the IronHorse is a allrounder in many different areas.





CUTCOACH

Caution, danger to life: Forest workers and rescue teams, fire brigades and rescue services are all too familiar with this problem: storm chaos. Fallen trees block the road or are under voltage. The risk of accident is particularly high for all parties involved when tree trunks are quickly and professionally removed.

The CutCoach has been a trusted teaching device for fire brigades, trade associations, rescue services and forestry educational institutions for many years.

Only experienced sawyers who quickly choose the safest cutting pattern can guarantee a smooth process. The proven CutCoach is a modern teaching device that offers the best possible training for real emergency situations.

In contrast to conventional voltage simulators, the "CutCoach" is equipped with a hydraulic system and enables efficient and user-friendly training on the device.



Technical details

Length	236,22 inches
Transport width	82,68 inches
Height	98,42 inches
Power connection	16 A CEE-plug
	If requested with
	petrol engine
Weight	5,500 lbs (Depending on
	the equipment)
Speed (Trailer) max.	50 mph
Hydraulic	
pump drive	4.4 hp electric engine
Operating	
pressure hydraulic	2,900 psi
Hydraulic	
pump power	15 Liter/Min.
Log length	153,54 inches
Log diameter	max. 15.75 inches

CUTCOACH









IRON HORSE

If you are often engaged with woodwork and maintenance on a rough terrain, the Iron Horse is an indispensable tool. The machine has a wide chain drive, is extremely agile and can be used in almost any terrain. For example you can use it to move logs in forests, where other forwarders can not be used.



Perfect allrounder for every purpose

The Iron Horse can easily be operated by one person and makes work much easier. Depending on its application area, you can choose for different equipment's for your needs. For example, the modern forwarder can have a telescopic crane and a motor cable winch.

Depending on the model, you have power up to 13hp. In forestry, professional garden landscaping or in agriculture, with the flexible allrounder you have decided for a modern working tool. Whether in case of moving wood or special precipitations, therewith you can significantly increase your efficiency in many areas.

Technical data

Engine	Honda 4 stroke engine
Performance	6,6 kW or 8,7 kW
	(depending on model)
Speed	7 km/h
Power transmission	Variator with centrifugal clutch
Fuel tank	6 Liter
Motor winch	20 m cable length, traction 700 - 1000 kg
Length	170 cm
Width	108 cm
Transport height	160 cm
Weight	ca. 420 kg (depending on model)





MADE IN GERMANY - MADE IN BAVARIA

- Research and development, electrical engineering and production in Rimsting, Germany
- Individual and customer-specific production
- Flexible implementation of special customer requirements
- Own welding, turning and milling center in the company
- Customer service on site
- Highly qualified and motivated employees






PROJECT PLANNING

Standard expansion modules

The following standard modules are available for facilitating the flow of wood on the log band saw: Log feeder with log separation, unloading arms, receivers, board separator, buffering station and roller conveyors.

All this modules are operated by the operator of the saw mill. Unloading arms and receivers are also available for mobile sawmills, with receivers being foldable.



PROJECT PLANNING









INTELLIGENT SUCCESS IS SUSTAINABLE SUCCESS.

AND CLEARLY A THING OF FORWARD-THINKERS.

All of our developments are characterized by a holistically thought-out, sustainable future perspective. For example, our saw production in Arnstadt, Germany which is equipped on 6.800 m² with most modern machines.

65 employees produce around 5 million linear meters of block and band saw blades per year and offer customers a comprehensive full service on band saw blades. The band saw blades are developed and optimized for its exact application which guarantees the best results with maximum quality and economy.

The band saw blades developed and optimized for the exact application guarantee the best results with maximum quality and economic efficiency.









SERVICE

Customer satisfaction and first-class service is particularly important at SERRA. We guarantee satisfaction. This is based on a few simple tenets:

- Each sawmill is individually designed with state of the art 3D CAD programs. We guarantee short delivery times while maintaining the same high quality. We offer a fast and reliable supply of spare parts through a global service.
- You can personally try out all sawmills under professional supervision at our demonstration hall. Your saw mill is unique. We manufacture each model according to your individual price and performance requirements. Once the device is fabricated, experienced professionals will personally instruct you on how to use your sawmill.
- You may request our mobile customer service at any time. We offer expert advice through our in-house hot-line. Free tips, suggestions and user experiences are shared in our practical online customer magazine SERRA INSIDE.



Export service

More than 50% of our production gets exported. Safely loaded and packed well in a container your customized machine will reach your home at any destination. World wide.

Calculation

You want to know how your SERRA saw mill gonna pay off? Have a look at the real figures.

Financing

Don't hesitate to contact us by requiring an offer with 0 % financing over a period of 6 months.







OVERVIEW OF SAWMILLS BY SERRA

All SERRA models comply with the strict safety standards of the EUROPEAN UNION with CEE symbols

	XE 160	XE 135	XT 135	SL 130i	ME 110
Max. Capacities					
Log length*	28" - 19.6 feet	28" - 19.6 feet	28 - 32 feet	28" - 52 feet	28" - 29 feet
Log diameter (A)	64.2"	52.3"	52.3"	41.9"	41.9"
Space above the sawblade (B)	27"	19"	19"	19"	20"
Space below the sawblade (C)	54"	44"	44"	44"	34"
Width of cut (D)	55"	39"	39"	39"	32"
Performance / 8 h**	15,000 BF	14,000 BF	14,000 BF	14,000 BF	11,800 BF
Main engine					
	43 hp electric	30 hp electric	25 hp electric	25 hp electric	25 hp electric
60	hp electric optional	43 hp electric optional	30 hp electric optional	30 hp electric optional	30 hp electric optional
Sawblades (Millimeter)					
Width	6"	4.75" - 5.5"	4.75" - 5.5"	4" - 4.75"	4" - 4.75"
Thickness	0.051"	0.043" - 0.047"	0.043" - 0.047"	0.043" - 0.047"	0.043" - 0.047"
Length	280" - 300"	217" - 237"	217" - 237"	217" - 237"	224"
Hydraulic equipment					
Log Handling	hydraulic	hydraulic	hydraulic	hydraulic	hydraulic
(loading, turning, clamping)					
Sawhead advance	electric/hydraulic	electric/hydraulic	electric/hydraulic	electric/hydraulic	electric/hydraulic
Height adjustments	electric	electric	electric	electric	electric
Sawblade guidance	hydraulic	hydraulic	hydraulic	hydraulic	hydraulic
Precutter	yes	yes	yes	yes	yes
Sawdust container	yes	yes	yes	yes	yes
Computer	yes	yes	yes	yes	yes
Automatic operation	yes	yes	yes	yes	yes
Weight***					
	only stationary	only stationary	up to 8,0 to	up to 3,5 to	up to 3,5 to

We are constantly working on advancing our development and technological improvements of our product line and to make them available to our customers. For this reason we reserve the right for technical changes as well as prices.

TECHNICAL DATA

OVERVIEW OF SAWMILLS BY SERRA

FE 50)	
24" - 141"	"	
21.6"	"	
7"	"	
18"	"	
15"	"	
2,000 BF	=	
5 hp electric	2	
1.375"	"	
0.035"	11	
122"	"	
manual	I	
manual	I	
manual	l	
manual	I	
no)	
0,28 to)	
	24" - 141' 21.6' 7' 18 15' 2,000 BF 5 hp electric 1.375' 0.035' 122' manua manua manua manua manua manua manua manua manua manua	24" - 141" 21.6" 7" 18" 15" 2,000 BF 5 hp electric 1.375" 0.035" 122" manual manual manual manual mo no no

